

DaimlerChrysler AG

Method for controlling the operation of a reversible
belt retractor in a motor vehicle

5

The invention relates to a method for controlling the operation of a reversible belt retractor to release a belt extraction lock of a restraint belt in a motor vehicle according to the precharacterizing clause of patent claim 1.

10

Conventional restraint belt systems in motor vehicles comprise a winding-up mechanism for automatically winding up the loose belt strap around a belt reel. The effect achieved by the automatic winding-up is that the belt, when put on, rests loosely and comfortably on an occupant's body and, when the seat belt is not in use, is rolled up around the belt reel (comfort-providing state). When the belt has been put on, the unwinding of the belt in the comfort-providing state is easily possible in order to provide the occupant with substantial freedom of movement. In this case, a small torque counter to the unwinding direction is produced by a retracting spring.

25

In particular so that a belt system of this type can restrain an occupant in the event of a collision, there is additionally a belt extraction lock. Above a specified acceleration of the belt reel in the unwinding direction and/or above a specified acceleration of the vehicle, this prevents the belt strap from being unwound. For this purpose, a belt-strap-sensitive sensor and a vehicle-sensitive sensor, which are generally part of the belt system, are provided. The response of one of these two sensors, for example of the vehicle-sensitive acceleration sensor, due to a vehicle acceleration above a threshold value prevents the belt strap from being unwound. Examples of

35

belt-strap-sensitive sensors are a mechanical centrifugal sensor coupled to the belt reel, an electromechanical centrifugal sensor or an electronic belt extraction sensor which detects the extraction
5 velocity of the belt strap or the acceleration thereof.

Some restraint belt systems also have a belt retractor, the operation of which can be controlled in order, in the case of an accident, to shorten the loose belt
10 strap and/or to pull an occupant toward the back rest of the seat into a position associated with a reduced risk of injury.

Some vehicles also make use of reversible belt
15 retractors which can be triggered repeatedly and also rapidly in succession. These reversible belt retractors can have different drives. For example, one reversible belt retractor can be driven by an electric motor which acts on the belt reel permanently or controllably via a
20 clutch. Other reversible belt retractors are driven by compressed air from a pressure reservoir or by a tensioned spring, the pressure reservoir being re-fillable during the driving operation and the spring being re-tensionable during the driving operation.
25 Reversible belt retractors of this type permit a tensioning of the seat belt at a specifiable strength, specifiable velocity and for a specifiable period of time. In particular, the capability of the reversible belt retractor to be repeatedly triggered makes a
30 preventive triggering of the same possible. A preventive triggering means that the belt retractor is triggered in safety-critical driving situations which are determined, for example, by sensors associated with the running dynamics or sensors associated with the
35 vehicle surroundings, or which are inferred by the evaluation of the brake pedal actuation, the steering angle or a driver's observation. In addition to a

preventive triggering, a reversible belt retractor may also be used for the haptic warning of the driver in safety-critical situations.

5 In the case of a preventive triggering of the belt retractor, which can take place before a collision is detected, or in the case of a triggering of the belt retractor for warning purposes, it is desirable that, after the tensioning has taken place, after the
10 hazardous situation has ended and during a guaranteed normal driving operation, the belt is released and again rests loosely and comfortably on the occupant. A guaranteed normal driving operation is present if the evaluation of the situation by a control device or a
15 hazard computer does not reveal that there is a safety-critical situation or if the condition necessary for triggering the belt retractor is no longer satisfied. Such a condition may be the presence or the absence of a certain signal on a data bus or a data line.

20 After a tensioning of the seat belt that is carried out by means of a belt retractor and a subsequent ending of the hazardous situation, which is recognized by means of the hazard computer, the situation may arise that,
25 because of a belt-strap-sensitive or a vehicle-sensitive sensor, which are generally coupled mechanically to the belt extraction lock, a desired extraction of the belt strap and therefore the return to the comfort-providing state is prevented.

30 A belt-strap-sensitive sensor may respond in particular if, after a tensioning of the belt, a release of a tensioned belt takes place while the latter is under a tensile load. If the unwinding of the belt strap takes
35 place too rapidly, then the belt-strap-sensitive sensor responds and the operation of the belt extraction lock is generally controlled mechanically and effectively.

The belt extraction lock also becomes effective if the vehicle-sensitive acceleration sensor responds because of the movement of the vehicle, for example in the case of a braking or steering maneuver, in the case of
5 severe swaying of the vehicle or in the case of rapid cornering. If the belt extraction lock is effective, then it is no longer possible to unwind the tensioned belt strap, and the freedom of movement of an occupant is highly restricted. The seat belt is therefore to be
10 transferred into the comfort-providing state again as rapidly as possible. This also applies if, after a reversible tensioning of the belt, the cause of the triggering of the belt retractor is no longer present and a normal driving operation is guaranteed. In order
15 to release the belt strap again, in the case of a blocking device, for example, which is customary in motor vehicles, a pawl has to be released from a blocking toothing. This is only possible if neither the vehicle-sensitive nor the belt-strap-sensitive sensor
20 activate the belt extraction lock.

A method for controlling the operation of a belt retractor with a blocking device is described in WO 02/46005. The belt retractor here acts, inter alia,
25 as a release device for releasing a belt extraction lock. This belt extraction lock acts on a belt reel in such a manner that, in the blocking state of the belt extraction lock, a belt strap wound up on the belt reel is prevented from unwinding, and only in the comfort-providing state is the unwinding of the belt strap
30 possible. The belt extraction lock can only change from the blocking state into the comfort-providing state when the vehicle-sensitive acceleration sensor does not detect any acceleration above an acceleration threshold
35 value. After the belt extraction lock comes into effect, the operation of the belt retractor is controlled by a release signal at a release time in

order to bring about the change of the belt extraction lock from the blocking state into the comfort-providing state.

5 WO 02/47049, which forms the generic type, discloses a method for controlling the operation of a reversible belt retractor to release a belt extraction lock of a restraint belt in a motor vehicle. After the hazardous situation which has been detected has been recognized
10 as being over, the operation of the belt retractor is controlled by a release signal at a release time in order to bring about the release of the belt extraction lock to shift it from the blocking state into the comfort-providing state. A variable characterizing the
15 running dynamics can be detected and used to determine the release time.

It is the object of the invention to improve the safety, the reliability and the comfort of a restraint
20 belt system with a reversible belt retractor. This object is achieved by the features of claim 1.

If a reversible belt retractor in a motor vehicle is triggered as a consequence of a hazardous situation
25 being detected, then a restraint belt of a belt system is tensioned. The belt system comprises a belt extraction lock which can be activated by an acceleration sensor and, in the activated state, has the effect of it not being possible for the restraint
30 belt to be unwound from a belt reel. By means of an algorithm based on a model of the acceleration sensor, and based on at least one variable characterizing the running dynamics, a release time for the release of the belt extraction lock to shift it from a blocking state
35 into a comfort-providing state is determined. After the end of the hazardous situation is determined, the operation of the belt retractor is controlled by a

release signal at the release time determined in order to permit the belt strap to be unwound freely and, if appropriate, to bring about the release of the belt extraction lock.

5

An advantage of the achievement according to the invention of the object is that reliable information about the actual state of the acceleration sensor is used in a simple manner by means of the algorithm based
10 on a model of the acceleration signal to determine the release time. By means of this reliable information about the actual state of the acceleration sensor, the release time can be defined in such a manner that, with specifiably, high probability, the acceleration sensor
15 does not cause the belt extraction lock to be brought into effect, i.e. that, with specifiably high probability, following the control of the operation of the reversible belt retractor at the release time, the belt strap is released for unwinding.

20

In an alternative embodiment of a reversible belt system, in addition to the first belt extraction lock already mentioned the belt system comprises a second belt extraction lock with a smaller retaining force.
25 This second belt extraction lock serves to prevent a simple unwinding of the reversibly tensioned belt strap, for example upon an habitual movement of an occupant. However, this second belt extraction lock is not suitable, in the case of an accident, for absorbing
30 the forces acting on the belt strap and for restraining the belt. The second belt extraction lock may be designed, for example, as a self-locking mechanism in the form of a worm mechanism. After a reversible tensioning of the belt, this second belt extraction
35 lock prevents the first, harder belt extraction lock with a high retaining force from becoming effective if additional, serious influences, such as, for example, a

collision of the vehicle, are absent. In the case of a belt system of this type, the second belt extraction lock is likewise released by the operation of the belt retractor being controlled at the release time
5 determined. The operation of a belt retractor of this type is controlled in the manner matched to the belt extraction lock, for example, in the case of a belt extraction lock with a worm mechanism, in such a manner that the self-locking mechanism is rotated in the
10 unwinding direction. However, the determination according to the invention of the release time is the same as in the case of a belt retractor without a second belt extraction lock of this type.

15 The release pulse generally serves to control the operation of a belt system to release a reversibly tensioned belt. In the case of other belt systems which are not illustrated, this may take place in different ways than the ways illustrated, but this is
20 insignificant regarding the fundamental advantages of the determination according to the invention of the release time.

In a refinement of the method for controlling the
25 operation of a reversible belt retractor, the release time is determined as being just a time at which the sensor model reveals that the acceleration detected by the acceleration sensor is smaller than a specifiable acceleration threshold value. This particularly
30 reliably prevents the belt extraction lock being effective due to an acceleration detected by the acceleration sensor at the release time.

In a further advantageous refinement, the release time
35 is determined as being a time at which the sensor model reveals that the acceleration detected by the acceleration sensor drops below or has already dropped

below a specifiable acceleration threshold value for at least a specifiable period of time. By this means, the release of the belt strap after the operation of the belt retractor is controlled at the release time can be
5 achieved with even greater reliability. The specifiable period of time is preferably a function of the change in acceleration and preferably also dependent on the vehicle model, the load, the tyres or other variables describing the driving situation.

10

The acceleration sensor is preferably a mechanical sensor and the sensor model is a mathematical model of the mechanical sensor. As an alternative to this, the sensor may also be an electromechanical sensor, an
15 electronic sensor or a sensor algorithm.

In order to determine the release time, in a refinement of the invention use is made of the transverse acceleration, the longitudinal acceleration, the wheel
20 speeds, the yaw velocity or the yaw acceleration. In particular, use is made of two or more of these variables in order to determine the release time. By means of these variables, an overall acceleration of the vehicle can be determined. If the acceleration
25 sensor of the belt system is a ball sensor acting isotropically in the plane of the vehicle, i.e. does not have a direction of preference in the plane of the vehicle, in particular the acceleration of the vehicle is determined in the plane. The acceleration
30 perpendicular to the plane of the vehicle may also enter into the determination of the release time.

In a simple refinement of the method for controlling the operation of a reversible belt retractor, the
35 release time is determined as being a time at which a plurality of the variables transverse acceleration, yaw velocity, yaw acceleration, wheel speeds and

longitudinal acceleration drop below a threshold value, which can be specified for the particular variable, for a specifiable period of time.

5 The single figure shows a flow diagram of an advantageous embodiment of a method for controlling the operation of a reversible belt retractor to release a belt extraction lock, which can be activated by an acceleration sensor, of a restraint belt. The operation
10 is controlled at a release time which is determined using wheel speeds, transverse acceleration and yaw acceleration. As an alternative or in addition, use may also be made of other variables for determining the release time.

15

In step 1, a wheel speed, or preferably a plurality of wheel speeds, is/are detected and, from the detected wheel speeds, the longitudinal acceleration of the vehicle is determined. As an alternative, the
20 longitudinal acceleration may also be determined in another manner or may be directly detected by means of a sensor. The longitudinal acceleration determined is made available for further processing in step 2. It is inquired in step 2 whether the longitudinal
25 acceleration is below a specifiable acceleration threshold value.

In step 3, the rotational acceleration of the vehicle about its own vertical axis is detected by sensor or is
30 determined by means of auxiliary variables, and is made available for further processing in step 4. In step 4, it may additionally be inquired whether the yaw velocity, the yaw acceleration or an auxiliary variable taking these two variables into consideration is below
35 a specifiable threshold value.

In step 5, the transverse acceleration of the vehicle

is detected or is determined by means of auxiliary variables, and is made available for further processing in step 6. In step 6, it is interrogated whether the transverse acceleration is below a specifiable
5 threshold value.

The results of the inquiries in steps 2, 4 and 6 are collated in step 7. A time is determined at which the monitored variables of longitudinal acceleration,
10 transverse acceleration and yaw acceleration are below the respectively specifiable threshold values. This determined time is defined as the release time.

In a special and particularly advantageous embodiment,
15 in step 7 the behavior of a ball within a ball sensor is simulated from the monitored variables. For this purpose, a model of the ball sensor is depicted in an algorithm and the monitored variables are used as input variables for the model.

20

Based on the variables determined or detected in steps 1, 3 and 5, both the current time and also a time in the future can be determined as a release time.

25 In step 8, further criteria which have to be satisfied for controlling the operation of the belt retractor to release a belt extraction lock are interrogated. For example, it is specified that a hazardous situation is no longer present, i.e. that the hazardous situation
30 which is the cause for the original triggering of the belt retractor is over. Furthermore, it is checked whether there is any other critical situation, and only if no such situation is present is, in step 9, the operation of the reversible belt retractor controlled
35 at the release time determined or within a specifiable period of time after the release time determined in order to release the belt extraction lock and therefore

to transfer the belt system from the blocking state into the comfort-providing state. In an alternative refinement, the inquiries carried out in step 8 may also take place at a different time, for example even
5 before step 1.